

Manual of Petroleum Measurement Standards Chapter 4—Proving Systems

Section 1—Introduction

THIRD EDITION, FEBRUARY 2005

REAFFIRMED: SEPTEMBER 2009



Manual of Petroleum Measurement Standards Chapter 4—Proving Systems

Section 1—Introduction

Measurement Coordination

THIRD EDITION, FEBRUARY 2005

REAFFIRMED: SEPTEMBER 2009



SPECIAL NOTES

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

API is not undertaking to meet the duties of employers, manufacturers, or suppliers to warn and properly train and equip their employees, and others exposed, concerning health and safety risks and precautions, nor undertaking their obligations under local, state, or federal laws.

Information concerning safety and health risks and proper precautions with respect to particular materials and conditions should be obtained from the employer, the manufacturer or supplier of that material, or the material safety data sheet.

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. Sometimes a one-time extension of up to two years will be added to this review cycle. This publication will no longer be in effect five years after its publication date as an operative API standard or, where an extension has been granted, upon republication. Status of the publication can be ascertained from the API Measurement Coordination Department [telephone (202) 682-8000]. A catalog of API publications and materials is published annually and updated quarterly by API, 1220 L Street, N.W., Washington, D.C. 20005.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this standard or comments and questions concerning the procedures under which this standard was developed should be directed in writing to the standardization manager, American Petroleum Institute, 1220 L Street, N.W., Washington, D.C. 20005. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the general manager.

API standards are published to facilitate the broad availability of proven, sound engineering and operating practices. These standards are not intended to obviate the need for applying sound engineering judgment regarding when and where these standards should be utilized. The formulation and publication of API standards is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 1220 L Street, N.W., Washington, D.C. 20005.

Copyright ©2005 American Petroleum Institute

FOREWORD

Chapter 4 of the *Manual of Petroleum Measurement Standards* was prepared as a guide for the design, installation, calibration, and operation of meter-proving systems commonly used by the majority of petroleum operators. The devices and practices covered in this chapter may not be applicable to all liquid hydrocarbons under all operating conditions. Other types of proving devices that are not covered in this chapter may be appropriate for use if agreed on by the parties involved.

The information contained in this edition of Chapter 4 supersedes the information contained in the previous edition (First Edition, May 1978), which is no longer in print. It also supersedes the information on proving systems contained in API Std 1101 *Measurement of Petroleum Liquid Hydrocarbons by Positive Displacement Meter* (First Edition, 1960); API Std 2531 *Mechanical Displacement Meter Provers*; API Std 2533 *Metering Viscous Hydrocarbons*; and API Std 2534 *Measurement of Liquid Hydrocarbons by Turbine-Meter Systems*, which are no longer in print.

This publication is primarily intended for use in the United States and is related to the standards, specifications, and procedures of the National Institute of Standards and Technology (NIST). When the information provided herein is used in other countries, the specifications and procedures of the appropriate national standards organizations may apply. Where appropriate, other test codes and procedures for checking pressure and electrical equipment may be used.

For the purposes of business transactions, limits on error or measurement tolerance are usually set by law, regulation, or mutual agreement between contracting parties. This publication is not intended to set tolerances for such purposes; it is intended only to describe methods by which acceptable approaches to any desired accuracy can be achieved.

Chapter 4 now contains the following sections:

- Section 1—"Introduction"
- Section 2—"Displacement Provers"
- Section 4—"Tank Provers"
- Section 5—"Master-Meter Provers"
- Section 6—"Pulse Interpolation"
- Section 7—"Field-Standard Test Measures"
- Section 8—"Operation of Proving Systems"
- Section 9—"Calibration of Provers"

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any federal, state, or municipal regulation with which this publication may conflict.

Suggested revisions are invited and should be submitted to the standardization manager, American Petroleum Institute, 1220 L Street, N.W., Washington, D.C. 20005.

CONTENTS

	Page
1 SCOPE.....	1
2 REFERENCED PUBLICATIONS.....	1
3 DEFINITION OF TERMS	1
4 LIQUID METERING HIERARCHIES	1
4.1 Overview of Hierarchy	1
4.2 Uncertainty Limits within the Hierarchy.....	2
5 PROVING AND METER FACTOR	3
5.1 General Considerations	3
5.2 Objectives.....	3
5.3 Procedures	3
5.4 Accuracy	3
6 TYPES OF PROVERS	3
6.1 Displacement Provers	3
6.2 Tank Provers.....	4
6.3 Master Meter Provers.....	4
7 CALIBRATION OF PROVERS.....	4
Tables	
1 General Liquid Metering Hierarchy Levels	2
2 Uncertainty Indices for General Liquid Metering Hierarchy	2
3 Hypothetical Uncertainty Limits in General Liquid Metering Hierarchy	2

Manual of Petroleum Measurement Standards

Chapter 4—Proving Systems

SECTION 1—INTRODUCTION

1 Scope

Section 1 is a general introduction to the subject of proving. The requirements in Chapter 4 are based on customary practices that evolved for crude oils and products covered by API *MPMS* Ch. 11.1. The prover and meter uncertainties should be appropriate for the measured fluids and should be agreeable to the parties involved.

2 Referenced Publications

Several documents served as references and as a resource of information in the revision of this standard.

Manual of Petroleum Measurement Standards

Chapter 1—“Vocabulary”

Chapter 4—“Proving Systems”

Chapter 5—“Metering”

Chapter 7—“Temperature Determination”

Chapter 11.1—“Physical Properties Data”

Chapter 12—“Calculation of Petroleum Quantities”

Chapter 13—“Statistical Aspects of Measuring and Sampling”

3 Definition of Terms

Terms used in this chapter are defined in 3.1 through 3.9.

3.1 calibration: The procedure used to determine the volume of a prover.

3.2 meter proof: The multiple passes or round trips of the displacer in a prover for purposes of determining a meter factor.

3.3 meter prover: An open or closed vessel of known volume that is used as a volumetric reference standard for the calibration of meters in liquid petroleum service. Such provers are designed, fabricated, and operated within the recommendations of Chapter 4.

3.4 meter pulse: A single electrical pulse generated by flow induced effects in the meter. The flow induced effects are normally caused by movement of physical elements within the meter’s primary flow element but may be caused by other flow induced effects that are proportional to flow rate. The pulses produced by the meter shall not be multiplied to

increase the number of pulses to conform to the requirements of Chapter 4.

3.5 prover pass: One movement of the displacer between the detectors in a prover.

3.6 prover round trip: The forward and reverse passes in a bi-directional prover.

3.7 proving: The procedure used to determine a meter factor.

3.8 standard conditions: *60°F and atmospheric pressure.*

4 Liquid Metering Hierarchies

4.1 OVERVIEW OF HIERARCHY

Liquid metering systems designed and operated in conformance with API’s *Manual of Petroleum Measurement Standards* typically have one or more of the following levels of hierarchy as shown in Table 1.

Level 1.

Primary standards involve mass, volume, and/or density standards developed and/or maintained by National Institute of Standards and Technology (NIST) and/or other national laboratories to calibrate secondary working standards.

Level 2.

Secondary working standards include mass, volume, density, and/or weighing systems maintained by NIST and/or other national laboratories to calibrate field transfer standards conforming to Chapter 4.7. Secondary working standards may also be maintained by state and other certified metrology laboratories to calibrate field transfer standards.

These additional secondary working standards, however, increase uncertainty in the final custody transfer quantities.

Level 3.

Field transfer standards conforming to Chapter 4.7 are devices used to calibrate meter provers conforming to Chapters 4.2, 4.3, and 4.4.

Level 4.

Meter provers conforming to Chapter 4 are used to determine meter factors that correct the indicated volumes of meters.

Table 1—General Liquid Metering Hierarchy Levels

Levels	Description of Hierarchy Level
1	Primary Standards
2	Secondary Working Standards
3	Field Standard Test Measures
4	Meter Prover
5	Meter Assembly (Indicated Volume)
6	Corrections for Quality and/or Quantity
7	Custody Transfer Ticket (Net Standard Volume)

Levels 5, 6, & 7.

Compositional analyses, where appropriate, together with the meter factor, is used to make corrections in the quality and/or quantity of the indicated volume of the meter, to determine the net standard volume being metered for custody transfer purposes.

When practical, the number of levels in a hierarchy should be kept to a minimum to keep uncertainty low. Each level in the hierarchy will increase the uncertainty of subsequent levels and eventually the final custody transfer quantity.

4.2 UNCERTAINTY LIMITS WITHIN THE HIERARCHY

Each level within a hierarchy will include all the errors and uncertainties from the previous or higher levels of the hierarchy. Therefore, uncertainties will always increase throughout each level of the hierarchy. Exact, defined, and rigorous procedures must be developed and followed exactly through each level of a hierarchy so that the uncertainty in the final level of the hierarchy is not higher than specified and still tolerable for commercial purposes. For levels in the hierarchy that exhibit randomness because of the intrinsic random nature of the activity or equipment, error or uncertainty may be limited to twice or less than the uncertainty in the previous level. For levels that are performed infrequently in the hierarchy, such as primary standards, the next level in the hierarchy, such as secondary working standards, may have uncertainty limits that are up to four times the previous level in the hierarchy. In the general hierarchy shown in Table 2, uncertainty indices are used to indicate the ratio of uncertainty of one level compared to the primary standard.

The effects of time should also be included in establishing limits within a hierarchy. Most custody transfer contracts or arrangements are in effect for years between two or more parties; therefore, the effects of random uncertainties to propagate to lower average values with time should be considered. Frequently, repeated activities may have uncertainty limits that are closer to the adjacent level in the hierarchy if rigorous procedures are developed and implemented that minimize

additional uncertainties. In the hierarchy of Table 2, the uncertainty index for meter indicated volume and corrections for quantity, such as the meter factors, can be lower than indicated in Table 2. An uncertainty index of 16 – 24 or lower for meter indicated volume is obtainable over the period of a year or longer. A lower uncertainty index over time for the custody transfer ticket of 32 – 48 is also obtainable from rigorous and frequently performed activities.

If the uncertainty limit for the average of custody transfer over one year is prescribed as $\pm 0.10\%$, the possible hypothetical corresponding uncertainty limits for each of the levels in the hierarchy are presented in Table 3.

Within each of the hierarchy levels there are other activities that are sources of error that must be identified and limited so that they do not disrupt the integrity of the hierarchy. These activities include procedures for calibrating the secondary working standards, field transfer standards, and meter provers. Rigorous procedures must be developed and followed so that these additional sources of uncertainties do not disrupt the uncertainty control within the hierarchy.

Table 2—Uncertainty Indices for General Liquid Metering Hierarchy

Level	Description of Hierarchy Level	Uncertainty Indices	
		Per Event	Average with Time
1	Primary Standards	1	1
2	Secondary Working Standards	2 – 4	2 – 4
3	Field Transfer Standards	4 – 16	4 – 8
4	Meter Prover Base Volume	8 – 32	8 – 16
5	Meter Indicated Volume	16 – 64	16 – 24
6	Correction for Quality and/or Quantity	32 – 128	24 – 32
7	Custody Transfer Ticket	64 – 256	32 – 48

Table 3—Hypothetical Uncertainty Limits in General Liquid Metering Hierarchy

Level	Description of Hierarchy Level	Uncertainty Limit, + or – %	
		Per Event	Per Year
1	Primary Standards	0.002	0.002
2	Secondary Working Standards	0.005	0.005
3	Field Transfer Standards	0.015	0.015
4	Meter Prover Base Volume	0.03	0.03
5	Meter Indicated Volume	0.10	0.05
6	Correction for Quality and/or Quantity	0.15	0.07
7	Custody Transfer Ticket	0.20	0.10

5 Proving and Meter Factor

The purpose of proving a meter is to determine its meter factor. The *meter factor* is obtained by dividing the prover volume by the indicated volume of the meter, both corrected to the standard conditions.

The purpose of a meter factor is to correct a meter's indicated volume. Obtaining a meter factor is an essential step in calculating the net standard volume of a receipt or delivery of petroleum liquids.

Because all calculations involve one or more corrections, and because the computation of numerous correction factors can lead to small differences if the computations are not carried out in a standard way, the calculations of petroleum quantities in dynamic measurement is covered in *API MPMS Ch. 12.2*. Refer to Chapter 12.2 whenever one or more of the following items must be calculated:

- a. Volumes in the provers.
- b. Meter factors.
- c. Measurement tickets.

5.1 GENERAL CONSIDERATIONS

All meters should be proved with the liquid to be measured and at the operating flow rate, pressure, and temperature. A meter that is used to measure several different liquids should be proved with each liquid. For additional details see *API MPMS Ch. 4.8*.

Meter proving shall be performed with a high degree of precision. The many details of the meter, its auxiliary equipment, and the proving system can contribute to measurement uncertainty. Likewise, there are difficulties in determining the physical properties of the measured liquid, pressure, temperature, and the presence of trapped air. Thorough inspections of provers and their components should be made routinely to ensure the reproducibility of proving results. See *API MPMS Ch. 12* and *API MPMS Ch. 13* for applicable calculation methods.

5.2 OBJECTIVES

Meter proving has two general objectives depending on the type of service.

- a. A meter is proved to determine its meter factor. The meter factor is applied to the indicated volume to compute the gross standard volume that is delivered through the meter. This is normal practice for pipeline and oil production operations. Results of the meter proving can be used to evaluate the performance or condition of the meter and/or prover.
- b. A meter is proved to adjust its registration, if necessary, to give a meter factor as close to 1.0000 (unity) as practical. The meter's indicated volume will be the volume of liquid actually delivered (gross volume) within allowable tolerances. This is the normal practice for meters that operate on inter-

mittent deliveries, such as tank-truck meters or loading-rack meters at terminals or bulk plants.

5.3 PROCEDURES

Meter proving can be classified according to the following procedures:

- a. The running start-and-stop procedure requires that the opening and closing meter readings of the proof be obtained while the meter is in operation. If the meter-proving registration is derived from something other than the meter register, steps shall be taken to ensure that all volumes indicated by the proving counter are also reflected in the meter register.
- b. The standing start-and-stop procedure uses the meter register or meter-proving counter, from which the opening and closing readings are obtained at no-flow conditions. If the flow is started too rapidly, pressure in the piping may momentarily fall below the vapor pressure of the liquid, causing some vapor to pass through the meter. This may damage the meter and result in inaccurate meter registration. Too rapid a change of liquid velocity may cause hydraulic shock.

5.4 ACCURACY

Accuracy is the ability of a measuring instrument to indicate values closely approximating the true value of the quantity measured. The accuracy of any calculated meter factor is limited by at least the following considerations:

- a. Prover calibration uncertainty.
- b. Meter proving procedural uncertainties.
- c. Equipment performance.
- d. Errors that arise from observation (spurious error).
- e. Errors that are implicit in the computation used to correct a measurement to standard conditions.

Abbreviated tables, non-standardized rounding of conversion factors, or intermediate calculations (see *API MPMS Ch. 12.2* for standardized calculations) can adversely affect the consistency of calculations. The observed and computed data for all meter proofs that are made to obtain a meter factor or another expression of meter performance shall be reported on a suitable meter-proving report form; examples are provided in *API MPMS Ch. 12.2*.

6 Types of Provers

6.1 DISPLACEMENT PROVERS

A displacement prover includes a calibrated section in which a displacer travels with the flow, activating detection devices. Proving procedure requires a resolution of one part in 10,000 (0.0001). A displacement prover may have an adequate volume to accumulate a minimum of 10,000 whole unaltered meter pulses between detector switches for each pass of the displacer. When the prover volume is inadequate

to generate 10,000 whole unaltered meter pulses for each pass of the displacer, the meter factor calculation requires pulse interpolation to increase the resolution to one part in ten thousand parts (0.0001). For pulse interpolation see API *MPMS* Ch. 4, Section 6.

6.2 TANK PROVERS

A tank prover is a volumetric vessel that has a reduced cross section or neck located at both the top and bottom or, in some cases, at the top only. These necks are equipped with gauge glasses and graduated scales. Tank provers may be open to the atmosphere, or they may be closed pressurized vessels. Proving by a tank prover employs the standing start-and-stop method (that is, the flow through the meter must come to a complete stop at the beginning and end of each

proving run). For more detailed information on tank provers see API *MPMS* Ch. 4, Section 4.

6.3 MASTER METER PROVERS

A master meter prover is a meter that is proved by a certified prover. A certified prover is a prover calibrated by water-draw method. The master meter is used to calibrate other provers or meters. For more detailed information on master meter provers, see API *MPMS* Ch. 4, Section 5 and Section 9.3.

7 Calibration of Provers

For procedure and calculation, refer to API *MPMS* Ch. 4, Section 9 and Ch. 12, Section 2 Parts 4 and 5.



**American Petroleum Institute
2005 Publications Order Form**

Effective January 1, 2005.

API Members receive a 30% discount where applicable.

The member discount does not apply to purchases made for the purpose of resale or for incorporation into commercial products, training courses, workshops, or other commercial enterprises.

Available through Global Engineering Documents:

Phone Orders: 1-800-854-7179 (Toll-free in the U.S. and Canada)
303-397-7956 (Local and International)

Fax Orders: 303-397-2740

Online Orders: www.global.ihs.com

Date: _____

API Member (Check if Yes)

Invoice To (Check here if same as "Ship To")

Name: _____
Title: _____
Company: _____
Department: _____
Address: _____

City: _____ State/Province: _____
Zip/Postal Code: _____ Country: _____
Telephone: _____
Fax: _____
E-Mail: _____

Ship To (UPS will not deliver to a P.O. Box)

Name: _____
Title: _____
Company: _____
Department: _____
Address: _____

City: _____ State/Province: _____
Zip/Postal Code: _____ Country: _____
Telephone: _____
Fax: _____
E-Mail: _____

Quantity	Product Number	Title	SO★	Unit Price	Total
	H04023	API MPMS Chapter 4.2, Displacement Provers		\$101.00	
	H04042	API MPMS 4.4, Tank Provers		\$66.00	
	H04052	API MPMS 4.5, Master-meter Provers		\$53.00	
	H04062	API MPMS 4.6, Pulse Interpolation		\$53.00	
	H04072	API MPMS 4.7, Field-standard Test Measures		\$66.00	
	H04081	API MPMS 4.8, Operation of Proving Systems		\$87.00	

Payment Enclosed **P.O. No.** (Enclose Copy) _____

Charge My Global Account No. _____

VISA **MasterCard** **American Express** **Diners Club** **Discover**

Credit Card No.: _____

Print Name (As It Appears on Card): _____

Expiration Date: _____

Signature: _____

Subtotal	
Applicable Sales Tax (see below)	
Rush Shipping Fee (see below)	
Shipping and Handling (see below)	
Total (in U.S. Dollars)	

★ To be placed on Standing Order for future editions of this publication, place a check mark in the SO column and sign here:

Pricing and availability subject to change without notice.

Mail Orders – Payment by check or money order in U.S. dollars is required except for established accounts. State and local taxes, \$10 processing fee*, and 5% shipping must be added. Send mail orders to: **API Publications, Global Engineering Documents, 15 Inverness Way East, M/S C303B, Englewood, CO 80112-5776, USA.**

Purchase Orders – Purchase orders are accepted from established accounts. Invoice will include actual freight cost, a \$10 processing fee*, plus state and local taxes.

Telephone Orders – If ordering by telephone, a \$10 processing fee* and actual freight costs will be added to the order.

Sales Tax – All U.S. purchases must include applicable state and local sales tax. Customers claiming tax-exempt status must provide Global with a copy of their exemption certificate.

Shipping (U.S. Orders) – Orders shipped within the U.S. are sent via traceable means. Most orders are shipped the same day. Subscription updates are sent by First-Class Mail. Other options, including next-day service, air service, and fax transmission are available at additional cost. Call 1-800-854-7179 for more information.

Shipping (International Orders) – Standard international shipping is by air express courier service. Subscription updates are sent by World Mail. Normal delivery is 3-4 days from shipping date.

Rush Shipping Fee – Next Day Delivery orders charge is \$20 in addition to the carrier charges. Next Day Delivery orders must be placed by 2:00 p.m. MST to ensure overnight delivery.

Returns – All returns must be pre-approved by calling Global's Customer Service Department at 1-800-624-3974 for information and assistance. There may be a 15% restocking fee. Special order items, electronic documents, and age-dated materials are non-returnable.

***Minimum Order** – There is a \$50 minimum for all orders containing hardcopy documents. The \$50 minimum applies to the order subtotal including the \$10 processing fee, excluding any applicable taxes and freight charges. If the total cost of the documents on the order plus the \$10 processing fee is less than \$50, the processing fee will be increased to bring the order amount up to the \$50 minimum. This processing fee will be applied before any applicable deposit account, quantity or member discounts have been applied. There is no minimum for orders containing only electronically delivered documents.

There's more where this came from.

The American Petroleum Institute provides additional resources and programs to the oil and natural gas industry which are based on API® Standards. For more information, contact:

- API Monogram® Licensing Program Phone: 202-962-4791
Fax: 202-682-8070
- American Petroleum Institute Quality Registrar (APIQR®) Phone: 202-962-4791
Fax: 202-682-8070
- API Spec Q1® Registration Phone: 202-962-4791
Fax: 202-682-8070
- API Perforator Design Registration Phone: 202-962-4791
Fax: 202-682-8070
- API ISO/TS 29001 Registration Phone: 202-962-4791
Fax: 202-682-8070
- API Training Provider Certification Program Phone: 202-682-8490
Fax: 202-682-8070
- Individual Certification Programs Phone: 202-682-8064
Fax: 202-682-8348
- Engine Oil Licensing and Certification System (EOLCS) Phone: 202-682-8516
Fax: 202-962-4739
- API PetroTEAM™ (Training, Education and Meetings) Phone: 202-682-8195
Fax: 202-682-8222

Check out the API Publications, Programs, and Services Catalog online at www.api.org.



Helping You Get
The Job Done Right.®

Additional copies are available through Global Engineering Documents at (800) 854-7179 or (303) 397-7956

Information about API Publications, Programs and Services is available on the World Wide Web at: <http://www.api.org>



**American
Petroleum
Institute**

1220 L Street, Northwest
Washington, D.C. 20005-4070
202-682-8000

Product No. H04013