

# Specification for Oil Field Chain and Sprockets

## Upstream Segment

API SPECIFICATION 7F  
SEVENTH EDITION, JANUARY 2003  
EFFECTIVE DATE JUNE 1, 2003

**REFERENCE  
ONLY**



American  
Petroleum  
Institute

**Helping You  
Get The Job  
Done Right.™**

## SPECIAL NOTES

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

API is not undertaking to meet the duties of employers, manufacturers, or suppliers to warn and properly train and equip their employees, and others exposed, concerning health and safety risks and precautions, nor undertaking their obligations under local, state, or federal laws.

Information concerning safety and health risks and proper precautions with respect to particular materials and conditions should be obtained from the employer, the manufacturer or supplier of that material, or the material safety data sheet.

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. Sometimes a one-time extension of up to two years will be added to this review cycle. This publication will no longer be in effect five years after its publication date as an operative API standard or, where an extension has been granted, upon republication. Status of the publication can be ascertained from the API Upstream Segment [telephone (202) 682-8000]. A catalog of API publications and materials is published annually and updated quarterly by API, 1220 L Street, N.W., Washington, D.C. 20005.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this standard or comments and questions concerning the procedures under which this standard was developed should be directed in writing to the standardization manager, American Petroleum Institute, 1220 L Street, N.W., Washington, D.C. 20005. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the general manager.

API standards are published to facilitate the broad availability of proven, sound engineering and operating practices. These standards are not intended to obviate the need for applying sound engineering judgment regarding when and where these standards should be utilized. The formulation and publication of API standards is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

*All rights reserved. No part of this work may be reproduced, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 1220 L Street, N.W., Washington, D.C. 20005.*

## FOREWORD

This specification is under the jurisdiction of the API Subcommittee on Standardization of Drilling and Servicing Equipment.

The purpose of this specification is to provide standards for roller chains suitable for use in oil field drilling and producing operations.

Much of the engineering material pertaining to roller chains and sprockets was taken from ASME B29.1 *Precision Power Transmission Roller Chains, Attachments and Sprockets*; and the book, published by the American Chain Association, *Chains for Power Transmission and Material Handling*. Additionally, portions of the standard ASME B29.1 are requirements of this specification as referenced herein.

Some of the performance related characteristics of the chains that are contained in this document are specific to oil field chains and to their application to oil field drives. This information cannot be found in other publications and imposes performance testing that goes beyond the basic requirements found in any other standards or specifications.

A section on drive design has not been included in this edition of the specification due to the great variety of applications and the complexity of the subject drives.

Conversions of U.S. customary units to International System (SI) metric units are provided throughout the text of this specification in parentheses, e.g., 6 in. (152.4 mm). SI equivalents have also been included in all tables. Formulas and certain relationships are intentionally presented only in U.S. customary units to preclude any ambiguity between them and tabulated values. Conversion factors are provided below if SI equivalents are desired for the calculated unit values.

U.S. customary units are in all cases preferential and shall be standard in this specification. Products are to be marked in the units in which ordered unless there is an agreement to the contrary between the purchaser and the manufacturer.

1 in. (in.)	= 25.4 millimeters (mm) exactly
1 foot (ft)	= 0.3048 meters (m) exactly
1 pound force (lbf)	= 4.448222 Newtons (N)
1 foot-pound force (ft•lbf) torque	= 1.355818 Newton-meters (N•m)
1 horsepower (hp) (550 ft•lbf/s)	= 0.7456999 kilowatts (kW)
1 gallon per minute (gpm)	= 0.0630920 cubic decimeters/second (dm <sup>3</sup> /s)

The following formula was used to convert degrees Fahrenheit (F) to degrees Celsius (C):

$$C = \frac{5}{9}(F - 32)$$


API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them, however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any federal, state, or municipal regulation with which this publication may conflict.

Suggested revisions are invited and should be submitted to the general manager of the Upstream Segment, American Petroleum Institute, 1220 L Street, N.W., Washington, D.C. 20005.

## CONTENTS

		Page
1	SCOPE	1
1.1	Coverage	1
1.2	Policy	1
2	REFERENCES	1
3	ROLLER CHAIN	1
3.1	Chain Designation	1
3.2	Heavy Series Chains	1
3.3	Dimensions	1
3.4	Chain Length Tolerance	1
3.5	Tensile Strength	1
3.6	Preloading	2
3.7	Minimum Press-out Force (Table 1)	2
3.8	Minimum Dynamic Strength	3
3.9	Marking Requirements	3
	APPENDIX A RECOMMENDED PRACTICE FOR INSTALLATION, LUBRICATION, AND MAINTENANCE OF ROLLER CHAIN DRIVES	5
	APPENDIX B SPROCKETS FOR ROLLER CHAIN	19
	APPENDIX C USE OF THE API MONOGRAM	21
 Figures		
	Chain Assembly	1
A-1	Align Shafts	5
A-2	Align Sprockets	5
A-3	Mid-Span Movement	6
A-4	Lubricant Flow Into the Chain Joint	7
A-5	Application of Lubricant to Chain	7
A-6	Drip Feed Lubrication	8
A-7	Oil Bath Lubrication	8
A-8	Slinger Disc Lubrication	9
A-9	Oil Stream Lubrication	9
A-10	Typical Oil Retaining Chain Casing	10
A-11	Casing Clearance Wear Limit	10
A-12	Chain Casing Schematic	11
A-13	Approximation of Temperature Rise of a Chain Casing	11
A-14	Measurement of Chain for Wear Elongation	14
A-15	Worn Sprocket	14
B-1	Sprocket Types	19
B-2	Sprocket Tooth Profile	19
 Tables		
1	Table of Standard Chain Capacities	4
A-1	Recommended Oil Viscosities for Various Temperatures	7
A-2	Lubrication Type for Chain Size and Speed	8
A-3	Required Oil Flow for Chain Drives	9

CONTENTS



..... 13

..... 19

Vertical text or markings along the right edge of the page, possibly bleed-through from the reverse side.